

## LOOP POWER INDICATOR



Flame Proof



Panel 96 x 48



IP -65/55 Proof

## FEATURE

- ✦ 4-20mA DC Loop Current Input.
- ✦ 4 / 5 digit LED Loop Indicator.
- ✦ Programmable Range Selection.
- ✦ Weatherproof & Flame Proof Housing
- ✦ Fully Programmable Range with Decimal Selection.
- ✦ Loop Voltage Drop Less than 1.2 V

## TECHNICAL SPECIFICATIONS

INPUT	Input Type	Current : 4 ~ 20 mA DC
	Range Limits	-19999 To 99999 Programmable With Decimal Point Selection(4 & 5 Digit)
	Accuracy	+/- 0.1 % Of Span
	Input Loading	Max 5 Volt
	Input Mode	Linear Or Square Root.
INDICATION	Indication	Led Type : 4 & 5 Digit - Segment Led Display
PROGRAMMABLE PARAMETERS	Display Resolution	-1999 To 9999 Fully Configurable For Linear Input
	Programming Of Parameters	Through 4 Tactile Key
OTHER	Supply Voltage & Power Consumption	96 X 48 & Panel Mounted Or Flame Proof
	Supply Voltage & Power Consumption	Loop Power & 5 Volt Maximum
	Operating Ambient Temp. And Humidity	0~50 °C Below 90%, Non Condensing

## ORDERING INFORMATION :

UT-60		1	2
Housing		Digit	
Wall Mounted IP	P	5 Digit LED	5
Flame Proof	F	4 Digit LED	4
96 x 48 Panel	P		
Special Type	F		

## FLAME PROOF

Gas Group	I IIA IIB IIC as per IS 2148/1981
Enclose Certification	Enclosure is Certified by C.M.R.I. & CCOE
Display Glass	Clear Glass Tough type A as per IS 2206
Material of Constructions	Aluminum Alloy
Cable Entry	3 x 3/4 " ET